

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 March 2003 (20.03.2003)


PCT

(10) International Publication Number
WO 03/022038 A1

- (51) International Patent Classification⁷: **A01G 27/00**, 27/04
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **NIELSEN, Rune** [DK/DK]; Hedelundsvej 34, DK-5270 Odense N (DK).
- (21) International Application Number: **PCT/DK02/00578**
- (22) International Filing Date:
6 September 2002 (06.09.2002)
- (74) Agent: **BUDDE, SCHOU & OSTENFELD A/S**; Vester Søgade 10, DK-1601 København V (DK).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PA 2001 01311 7 September 2001 (07.09.2001) DK
- (81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (71) Applicant (for all designated States except US): **GARTNERIET PKM APS** [DK/DK]; Slettensvej 207, DK-5270 Odense N (DK).

[Continued on next page]

(54) Title: **CAPILAR CONTROLLED WATERING OF PLANTS**



(57) Abstract: The present invention relates to a method and container for the cultivation of ornamental plants, facilitating the application of the method of drought stress to reduce cell elongation of plants grown in a slowly absorbing material such as peat moss without the use of chemical retarding agents. The invention thus discloses a container for the cultivation of plants comprising a layered structure incorporating a rapidly liquid absorbing reservoir and a body of suitable cultivation substrate. According to an advantageous embodiment a layer is furthermore inserted between said reservoir and said cultivation substrate in order to obtain a controlled flow of liquid from said reservoir to said cultivation substrate.

WO 03/022038 A1



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

CAPILAR CONTROLLED WATERING OF PLANTSTECHNICAL FIELD

5

The present invention relates to a method and container for the cultivation of ornamental plants.

10 BACKGROUND OF THE INVENTION

A technique for controlling the cell elongation of plants with a reduced application of chemical retarding agents is known within the art as drought stress. The reduction of the application of chemical retarding agents is highly desirable from an environmental
15 point of view. Furthermore the durability of plants in which the growth has been retarded by the application of drought stress has been shown to be improved [1].

One of the problems with the application of a traditional cultivation substrate such as peat moss in connection with the application of the technique of drought stress is the
20 following:

The majority of pot plants commercially produced are grown in a traditional cultivation substrate such as peat moss. However peat moss suffers from a number of disadvantages which are especially serious in connection with the conditions
25 prevailing under drought stress. Specifically the ability of peat moss to absorb water is reduced when the moisture content of the peat moss is low. Consequently it becomes in practice difficult to approach the drought limit because this reduced ability to absorb water may prevent the driest plants from receiving water at all. A consequence of these watering problems is that the uniformity of the plants is reduced and hence an
30 increased waste of plants in a production is generally the result.

A typical problem in connection with watering of pot plants especially at the customer furthermore results from an excessively large supply of water resulting in the formation of a layer of water at the button of the flower pot and associated flower pot saucer. In
35 this case the roots of the plant in the pot will suffer from suffocation due to a lack of sufficient air supply to the roots. It would thus be advantageous to provide a bottom

portion in the flower pot into which portion the roots of the plant does not penetrate, the thickness of this bottom portion being for instance equal to or larger than the depth of an associated flower pot saucer.

5

DISCLOSURE OF THE INVENTION

Based on the above background of the invention it is an object of the present invention to provide a method and a container for the cultivation of plants which allows the
10 application of drought stress to control the cell elongation of plants without the application of chemical retarding agents which method and container does not give rise to the problems connected with the application of drought stress described above.

It is a further object of the present invention to provide a method and container for the
15 cultivation of plants which at least substantially solves the above mentioned problem of the risk of suffocation of the roots of the plants resulting from an excessive supply of water.

These and other objects are attained with a method according to independent claim 1
20 and a container according to independent claim 4. Various embodiments of the invention are defined in the dependent claims.

According to the invention a very accurate dosage of the cultivation liquid supply to each individual plant as required for instance when said technique of drought stress to
25 control the growth of plants is applied can be obtained by providing said pots or containers with a rapidly absorbing reservoir which can absorb a sufficient amount of cultivation liquid (i.e. water possibly mixed with a suitable fertiliser) from a supply of such cultivation liquid and thereafter gradually pass the absorbed cultivation liquid on to the plant(s) in said pot or container.

30

In the context of the present invention the term "rapidly absorbing" should simply means that the rapidly absorbing material is able to absorb a given quantity of liquid more rapidly than the cultivation substance used in the particular case will be able to absorb a similar quantity.

35

A possible way of implementing said rapidly absorbing reservoir is to provide a pot or container comprising one or more access openings for cultivation liquid at the bottom surface hereof with a layer of rapidly absorbing material immediately above these access openings, above which rapidly absorbing layer a layer of suitable cultivation substance containing a least a major portion of the roots of the plant is provided. The cultivation substance will absorb water and fertiliser directly from the reservoir layer at a slower rate than the rate by which liquid is absorbed from the liquid supply by the rapidly absorbing layer. In practice a number of materials can be suitable for each of these layers. One of the characteristics determining the rate of absorption of the material will be the dimension of the pores of the material, a large pore size providing a relatively more rapid absorption of liquid than a smaller pore size. A specific embodiment of a layered reservoir system of the above kind will be discussed in the detailed description of the invention.

Furthermore, if the above method and container is to be applied in connection with traditional watering systems in production plants in greenhouses, where the plants are supplied with water during a time interval of for instance 20 to 40 minutes, water may penetrate from the rapidly absorbing layer throughout the total volume of cultivation substrate and a controlled drought stress effect will not be obtained. If it in such production plants is required that only the rapidly absorbing layer be filled with water during the watering sessions means must be interposed between the rapidly absorbing layer and the cultivation substrate for controlling the flow of water from the rapidly absorbing layer to the cultivation substrate. According to one embodiment of the present invention this controlling means is provided by a thin layer of liquid impermeable material provided with a pattern of through holes providing controlled liquid communication between the rapidly absorbing layer and the cultivation substance. Other means such as a layer of showily liquid permeable material of sufficient thickness should also be used, and other equivalent means may be devised by a person skilled in the art without departing from the scope of the present invention as defined in the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in more detail with reference to the accompanying drawings, in which

Figure 1 is a cross-sectional view of a flowerpot comprising material according to a first embodiment the invention;

Figure 2 is a cross sectional view of a flower pot comprising material according to a second embodiment of the invention; and

- 5 Figure 3 is a graph over gross weight of container for a normal production method applying drought stress and for a similar method applying a container according to the present invention.

10 DETAILED DESCRIPTION OF THE INVENTION

In the following a detailed description of one embodiment of the invention is given.

- Referring to Figure 1 there is showed an embodiment of a pot 1 according to the present invention. The pot 1 comprises a number of access openings 3 distributed
15 over the bottom face 4 of the pot. Directly above these access openings 3 there is located said rapidly absorbing reservoir, which according to this embodiment consists of a layer 5 of a porous material with relatively large pores and hence the ability to rapidly absorb a liquid via the access openings 3 from a liquid source (not shown) and
20 also to contain a relatively large amount of such liquid. Above and in contact with the layer 5 there is provided a second porous layer 6 of a suitable cultivation substance such as peat moss with relatively smaller pores than layer 5. When the reservoir layer 5 has been filled with liquid the liquid is gradually sucked up into the cultivation layer 6, from where it is absorbed by the roots 7 of the plant 2.

25

- One advantage of the application of a pot of the kind described above is, that when drought stress is applied in a production process there will be no problems of providing the plants with cultivation liquid, even though the cultivation substance 6 initially is in a very dry state. Furthermore as the size of the pores in layer 5 is relatively large and in
30 layer 6 much smaller the additional advantageous side effect is obtained that the reservoir layer 5 will dry up faster than the cultivation layer 6, because the larger capillary rise pressure of the smaller pores of layer 6 empties this layer 5 for liquid, thus leaving a dry zone at the bottom of the pot. The roots 7 of the plant will therefore only penetrate a short distance into the dry reservoir layer and not fill up the bottom
35 portion of the pot. Thus in case of too large supply of liquid at the end user the roots

will not suffer from suffocation due to lack of air supply to the same extent as traditionally cultivated plants.

According to the above embodiment of the present invention the volume of the reservoir layer 5 will be approximately 20 to 25% of the total volume of the reservoir layer 5 and the cultivation substrate 6. Under certain circumstances the volume of the reservoir layer 5 may however be reduced to approximately 10% of the total volume (when the amount of liquid supplied during each watering session is to be very limited). A volume of the reservoir layer 5 of up to approximately 40% of the total volume may however be relevant in certain other cases.

Referring to Figure 2 there is shown a second embodiment of the present invention comprising a liquid flow controlling means interposed between the reservoir layer 5 and the cultivation substance 6. According to this embodiment said controlling means is provided by a thin film 8 made from a liquid impermeable material and provided by a suitable number of through holes 9 for liquid communication between the reservoir layer 5 and the cultivation layer 6. The flow of liquid can in this manner be controlled for instance through a proper dimensioning of the diameter of the holes 9 and the thickness of the foil 8 and also by the choice of the numbers of the holes 9.

20

Referring to Figure 3 here is shown a graph over the gross weight of a pot (i.e. the material in the pot and the plant) as a function of time for a traditional production system applying the drought stress technique for controlling the growth of plants but not applying pots with a reservoir layer according to the invention and for a production system applying pots according to the present invention. It is evident from the graph that there in case of traditionally drought stress grown plants will be large intervals of time (several days) after the supply of liquid has taken place, where no drought stress effect will occur at all. In fact only some 10 to 20 percent of the production time a drought stress effect will be obtained. On the other hand in case of applying pots according to the present invention in the production system it will be possible to increase and decrease the degree of drought stress by changing the lower weight limit determining whether liquid should be supplied. For a more detailed discussion of a possible production system applying pots or containers according to the invention reference is made to co-pending patent application entitled: "Production method and

35

system for ornamental plants", with the same applicant as the present application (application number will be inserted when available).

Although one embodiment of the present invention has been shown and described in the preceding parts of the detailed description it is understood that a person skilled in the art may conceive other embodiments of the invention without departing from the scope of the invention as defined by the following claims.

- 10 [1] Lise Andersen, Michelle H. Williams:
"Hold igen med vandingen"
Gartner tidende, bind 116, nr. 48, p.20-22, (2000).

15

20

25

30

35

CLAIMS:

1. A method for the supply of cultivation liquid to ornamental plants comprising the steps of:
- 5 (a) providing a body (6) of cultivation substrate containing at least a major part of the roots (7) of said ornamental plant (2);
- (b) providing a supply of said cultivation liquid;
- (c) providing a reservoir (5) for said cultivation liquid, said reservoir (5) being in liquid communication with said body (6) of cultivation substrate;
- 10 (d) establishment of liquid communication (3) from said supply of cultivation liquid to said reservoir (5), whereby said reservoir (5) absorbs an amount of said cultivation liquid and thereby becomes partially or completely filled with said cultivation liquid;
- (e) propagation of said cultivation liquid from said reservoir (5) to said body (6) of cultivation substrate.
- 15
2. A method according to claim 1, characterised in that the rate of said absorption of liquid by said reservoir (5) from said supply of cultivation liquid is greater than the rate of said propagation of said cultivation liquid from said reservoir (5) to said body (6) of cultivation substrate.
- 20
3. A method according to claim 1 or 2, characterised in that said liquid communication between said reservoir (5) and body of cultivation substrate (6) is controllable by the introduction of liquid communication control means (8, 9) between said reservoir (5) and said cultivation substrate (6).
- 25
4. A container for the cultivation of ornamental plants comprising a liquid absorbing reservoir (5) which can communicate (3) with a supply of said liquid and which reservoir (5) is furthermore in liquid communication with a body (6) of cultivation substrate suitable for the cultivation of said plants and containing at least the major
- 30 portion of the roots (7) of said plants (2).
5. A container according to claim 4, characterised in that said reservoir is formed as a layer (5) of thickness (d) and volume (V_R) positioned at the bottom portion of said container (1) in liquid communication with at least one access port (3) for the provision
- 35 of said liquid from said supply.

6. A container according to claim 4, characterised in that said liquid communication between said reservoir (5) and said body (6) of cultivation substrate is provided via a liquid impermeable layer (8) inserted between said reservoir (5) and said body (6) of cultivation substrate, said liquid impermeable layer (8) being provided with one or
5 more through holes (9).

7. A container according to claim 4, characterised in that said liquid communication between said reservoir (5) and said body (6) of cultivation substrate is provided via a liquid permeable layer (8) with suitable permeability inserted between said reservoir
10 (5) and said body (6) of cultivation substrate.

8. A container according to any preceding claims, characterised in that said reservoir (5) is formed by a rapidly absorbing porous material of a large first pore size.

15 9. A container according to any preceding claim, characterised in that said body (6) of cultivation substrate is formed by a material having a second pore size smaller than the pore size of said rapidly absorbing porous material forming said reservoir (5).

10. A container according to claim 4, characterised in that said reservoir (5) has a
20 volume (V_R) within the range 10% to 40% of the total volume of the reservoir layer (5) and the cultivation substrate (6).

11. A container according to claim 4, characterised in that said reservoir (5) has a
25 volume (V_R) within the range 20% to 25% of the total volume of the reservoir layer (5) and the cultivation substrate (6).

1/3




Fig. 1

2/3




Fig. 2

— Normal production

- - - Production according to the invention




Fig. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK 02/00578

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A01G27/00 A01G27/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A01G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 28 49 044 A (HOELTER HEINZ) 22 May 1980 (1980-05-22) claim 1; figure 1 ---	1-10
X	CH 675 941 A (HANSPETER ROOST DR MED) 30 November 1990 (1990-11-30) abstract; figure 1 ---	1-5,7-10
X	FR 2 599 934 A (BEEKENKAMP GERRIT) 18 December 1987 (1987-12-18) abstract; figure 1 ---	1-5,7-11
X	WO 92 04823 A (COLES FREDERICK CHARLES) 2 April 1992 (1992-04-02) abstract; figure 2 -----	1-5,7-10

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 November 2002

Date of mailing of the international search report

20 12 2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

INGRID FALK/JA A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/DK 02/00578

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 2849044	A	22-05-1980	DE 2849044 A1	22-05-1980
CH 675941	A	30-11-1990	CH 675941 A5	30-11-1990
FR 2599934	A	18-12-1987	FR 2599934 A1	18-12-1987
WO 9204823	A	02-04-1992	AU 8423591 A WO 9204823 A1	15-04-1992 02-04-1992

we have already